- SUBMERTEC LIMITED -



Unit 7, Castle Business Centre, Queensferry Road, Dunfermline, Fife, KY11 8NT, SCOTLAND Tel: +44 1383 626659 email: sales@submertec.co.uk www.submertec.co.uk

## HD INSPECTION SUPER SPYBALL CONTROL UNIT

## Model SS-CPI-2 for use with SSB-HDI Super Spyball

Portable Control Unit Model SS-CPI-2 has been developed to complement the HD Inspection Super Spyball and make full use of its unique features.

Weighing only 10Kg and housed in a durable yellow Polypropylene case, this unit which operates from 100 to 240 volts AC, provides control, display and HD recording from the Inspection Super Spyball.

The 17.3 inch TFT colour LCD display mounted in the case lid behind a scratch resistant Polycarbonate window displays a clear and bright image from the Spyball camera even in bright sunlight.

- 1080p HD Digital Video Recorder with HD Still Photos
- Simultaneous Record to internal 256GB & external USB
- Date and Time overlay
- Video Text overlay using USB Keyboard
- Microphone or Line input with built in playback speaker
- Joystick for proportional control of camera angle
- Dedicated Super Spyball control Display
- Automatic Panorama photos
- Option to display Super Spyball Depth and P&T angles
- GPS available as an option
  - HDMI output from camera available as an option

DVR Menu controls are provided for playback, copy, delete, file name, date & time format etc.

Super Spyball controls include focus, variable intensity LED lighting and Laser Control. Access is also provided to special functions such as invert joystick direction, set movement limits, camera exposure, panorama angles and many more.

The HDIL Illuminated camera can be connected in place of a Super Spyball for inspection inside pipes and confined spaces.

Please note that Super Spyball equipment is not compatible with the original black Spyballs or their cables.

MODEL SS-CPI-2 CONTROL UNIT SPECIFICATION	
Dimensions	490mm wide, 394mm deep and 190mm high (when closed)
Weight	10Kg (22lb)
Power Supply	100 to 240 volts AC at 3 Amps
Display	17.3 inch sunlight viewable colour active matrix TFT LCD
Controls	DVR and Super Spyball
DVR Files	Record 1080p MP4 and 1920x1080 JPG files
DVR Storage	Internal 256GB + External USB (FAT32 only)
File Size	Approx 2GB / Hour MP4 video & 500KB jpg Photo
Output	Audio Line Output & HDMI Option



Spyballs and Super Spyballs are available in a number of configurations and with control options to suit a range of tasks from inspection to aquaculture – please visit our web site at www.submertec.co.uk to view these together with other Submertec products.

Note: Specification may change without notice.

